




Walkstool spare parts

Instructions for attaching a new rubber foot

1. Remove the old rubber foot if it is still attached.

2. The lower leg should have a plastic end attached. If not, attach a plastic end to the lower leg by using a hammer. The plastic end will protect the rubber foot from being damaged by the aluminum tube.



3. Attach the rubber foot to the lower leg. Use a hammer for the last centimeter, as it is important that the rubber foot is fully attached to the lower leg.



Headoffice

SCANDINAVIAN TOUCH AB
BJÖRKALLÉN 17, SE-142 66 TRÅNGSUND, SWEDEN
PHONE +46 8 676 07 00
www.walkstool.com







Production & Administration





SCANDINAVIAN TOUCH AB
LINDHAGSGATAN 5C, SE-531 40 LIDKÖPING, SWEDEN
PHONE +46 510 255 55
E-MAIL info@walkstool.com



Walkstool®

Comfort models

					
1	2	3	4	5	6
Plastic stud	Seat	Plastic cup	Upper leg	Plastic joint	Center piece




			
7	8	9	10
Lower leg	Red spring	Plastic end	Rubber foot



Walkstool®

Basic models

					
1	2	3	4	5	6
Plastic stud	Seat	Plastic cup	Upper leg	Plastic joint	Center piece

		
7	8	9
Lower leg	Red spring	Plastic foot

